

**1** FILL SOLID WITH SOUND DEADENING MATERIAL

**2** CONTINUOUS ACOUSTICAL SEALANT

**3** SHIM AS REQUIRED TO SUIT ROUGH OPENING


**4** FACTORY PUNCH AND DIMPLE TRIM FRAME FOR # 8-32 F.H.M.S. @ 24" O.C. TRIM IS SCREWED TO FRAME. REMOVAL & REAPPLICATION OF TRIM FRAME IS BY INSTALLER.

**5** STUFF 1/4" CLEARANCE GAP WITH INSULATION BY INSTALLER

**6** THROAT DIMENSION OF FRAME IS NET WALL + 1/8" INSTALLATION CLEARANCE.  
\_\_\_\_\_ + \_\_\_\_\_ CLEARANCE= \_\_\_\_\_

**7** PUNCH & DIMPLE FOR 1/4" FLAT HEAD SCREW \*STAGGERED\* \_\_\_\_\_ PER JAMB \_\_\_\_\_ PER HEAD. Z & PIPE SPACER @ EACH SCREW LOCATION. NOTE: BOTTOM P & D MUST BE ON DOOR SIDE. (ANCHOR BOLTS FURNISHED BY INSTALLER)

**8** PRESSURE ANCHOR: 1 BELOW BOTTOM & CENTER HINGE, STRIKE JAMB SIMILAR. LOCATE TO FULLY ENGAGE SURFACE OF STUD



KRIEGER STEEL PRODUCTS  
Pico Rivera, CA  
(562)695-0645

Project No: \_\_\_\_\_

Date: \_\_\_\_\_

Drawn By: \_\_\_\_\_

Detail:  \_\_\_\_\_

Sheet: \_\_\_\_\_