

Model BD1

DETAILS¹

UL-752 ²	N.I.J. (0108.01)	Weapons Criteria	Shots
Level 1	Type I, II, II-A	9mm Parabellum (Luger) Pistol 124 gr. Full Metal Jacket at 1175 fps	3

DOWNLOADS

Generic Frame

DWG File	http://www.kriegerproducts.com/downloads/cad/dwg/BD1.dwg
DWF File	http://www.kriegerproducts.com/downloads/cad/dwf/BD1.dwf
PDF File	http://www.kriegerproducts.com/downloads/cad/pdf/BD1.pdf

NOTES

- Specification: http://www.kriegerproducts.com/downloads/doc/KSP_BulletAllSpec.doc
- This is a pre-engineered model. We custom manufacture to your actual needs.

LEDGEND

1. Hinge type on tested door for level 1, 2, 3, & 6 is a standard mortise butt hinge. Hinge type on tested door for level 4, 5, 7 & 8 is a Continuous Heavy Duty Hinge, prepared on door only, field drilling and tapping on frame by others.
2. KSP's Bullet Resistant Doors are available with up to 3 hour U/L label. We also offer positive pressure tests in accordance with Standards: U/L 10C and UBC 7-2 and 7-4. (Standard testing restrictions apply)