

Model BD4AP

DETAILS¹

UL-752 ²	N.I.J. (0108.01)	Weapons Criteria	Shots
None	Type VI	30-06 Springfield Rifle 166 gr. Armor Piercing (AP) bullet, velocity 2850f/sec.	1

DOWNLOADS

Generic Frame

DWG File	http://www.kriegerproducts.com/downloads/cad/dwg/BD4AP.dwg
DWF File	http://www.kriegerproducts.com/downloads/cad/dwf/BD4AP.dwf
PDF File	http://www.kriegerproducts.com/downloads/cad/pdf/BD4AP.pdf

NOTES

- Specification: http://www.kriegerproducts.com/downloads/doc/KSP_BulletAllSpec.doc
- This is a pre-engineered model. We custom manufacture to your actual needs.

LEDGEND

1. Hinge type on tested door for level 1, 2, 3, & 6 is a standard mortise butt hinge. Hinge type on tested door for level 4, 5, 7 & 8 is a Continuous Heavy Duty Hinge, prepared on door only, field drilling and tapping on frame by others.
2. KSP's Bullet Resistant Doors are available with up to 3 hour U/L label. We also offer positive pressure tests in accordance with Standards: U/L 10C and UBC 7-2 and 7-4. (Standard testing restrictions apply)